

Metering transmitter LoRa / LoRaWAN

TX meter reading - pulse meters



LoRa LoRaWAN™

RUGGED IP65 ENCLOSURE

EASY TO INSTALL

VERY LONG RANGE RADIO

REPLACEABLE BATTERY

VERY LONG BATTERY LIFE > 20 YEARS

SPECIFICATIONS

Enclosure and IP rating	ABS IP 65
Dimensions (l x w x h)	118 x 79 x 43 mm
Mounting	Wall / Collar / Din Rail (option)
Radio antenna	Embedded
Pulse interfaces	Dry contact & open collector
Inputs	2 pulse inputs (2 dry-contact inputs or 1 dry-contact input & 1 open collector input)
Pulse type	50ms min / 10Hz max
TX working temperature	- 20 / + 55°C
Power supply	Replaceable 3.6 V D Lithium battery - Low battery alert
Radio frequency band	868 MHz bidirectional
Radio protocol	LoRa – LoRaWAN
Output power	25mW (14 dBm)
Configuration / Installation	Via radio - LoRa mode : Embedded IP server - Mode change via jumper (provided)
Datalogging	Option
Battery autonomy / Periodicity	> 15 years battery life with 5 min periodicity / Configurable periodicity
ID	DEV EUI in LoRaWAN mode ; LoRa ID in private mode
LED	3 LED's
Approval	CE
Ordering code	TX PULSE 600-036

DTM50-b